MSi®

GeForce GTX 1660 SUPER™ GAMING X







SPECIFICATIONS

Model Name	GeForce® GTX 1660 SUPER™ GAMING X
Graphics Processing Unit	NVIDIA® GeForce® GTX 1660 SUPER™
Interface	PCI Express x16 3.0
Core Clocks	Boost: 1830 MHz
CUDA® CORES	1408 Units
Memory Speed	14 Gbps
Memory	6GB GDDR6
Memory Bus	192-bit
Output	DisplayPort x 3 (v1.4a) HDMI™ x 1(Supports 4K@60Hz as specified in HDMI™ 2.0b)
HDCP Support	2.2
Power consumption	125 W
Power connectors	8-pin x 1
Recommended PSU	450 W
Card Dimension (mm)	247 x 127 x 46 mm
Weight (Card / Package)	862g / 1460 g
DirectX Version Support	12 API
OpenGL Version Support	4.5
Afterburner OC	Y
Maximum Displays	4
VR Ready	Y
G-SYNC® technology	Υ
Adaptive Vertical Sync	Υ
Digital Maximum Resolution	7680x4320

FEATURES



MSI Afterburner

The ultimate overclocking software with advanced control options and real-time hardware monitor.



OC PERFORMANCE

MSI OC graphics cards are equipped with higher clock speeds out of the box for increased performance.



TORX FAN 3.0

Award-winning fan design combining two different fin designs for cool & quiet gaming.



ZERO FROZR

Eliminates fan noise by stopping the fans in low-load situations so you can focus on your game.



CUSTOM PCB

An optimized PCB design with enhanced power delivery provides a solid base for high performance gaming.



SOLID BACKPLATE

Increases toughness of the card to prevent bending while complementing the design.



Mastery of Aerodynamics

Using groundbreaking aerodynamic techniques, the heatsink is optimized for efficient heat dissipation.



DRAGON CENTER

A consolidated platform that offers all software including MYSTIC LIGHT functionality for your MSI Gaming product.

CONNECTIONS



- 1. DisplayPort
- 2. HDMI™